

ONE-PIECE CLAMPING COUPLINGS RECESSED SCREW **CC-SERIES**



- Recessed screw head provides an outside surface free of major projections
- High axial load and torque capacity
- Design fully engages the shaft without marring
- Greater axial holding power than set screw couplings
- Effective on both hard and soft shafts



For 3D Models & 2D Sales Drawings

DIMENSION
BORE, INCH

TOLERANCE
+0.003 / -0.000

PART NUMBER	PRODUCT SPECIFICATIONS						
	BLACK OXIDE STEEL	BORE	2ND BORE	OD	LENGTH	SCREW SIZE	APPROX WEIGHT (OZ)
CC-025-025		1/4	1/4	13/16	1 1/4	4-40 x 3/8	2.26
CC-037-025		3/8	1/4	1 1/16	1 5/8	6-32 x 3/8	5.13
CC-037-037		3/8	3/8	1 1/16	1 5/8	6-32 x 3/8	4.96
CC-050-037		1/2	3/8	1 1/4	1 7/8	8-32 x 1/2	8.11
CC-050-050		1/2	1/2	1 1/4	1 7/8	8-32 x 1/2	7.70
CC-062-050		5/8	1/2	1 1/2	2 1/4	10-32 x 1/2	13.30
CC-062-062		5/8	5/8	1 1/2	2 1/4	10-32 x 1/2	22.40
CC-075-050		3/4	1/2	1 3/4	2 5/8	1/4-28 x 5/8	22.00
CC-075-062		3/4	5/8	1 3/4	2 5/8	1/4-28 x 5/8	22.00
CC-075-075		3/4	3/4	1 3/4	2 5/8	1/4-28 x 5/8	20.90
CC-087-062		7/8	5/8	1 7/8	2 7/8	1/4-28 x 5/8	27.40
CC-087-087		7/8	7/8	1 7/8	2 7/8	1/4-28 x 5/8	25.40
CC-100-050		1	1/2	2	3	1/4-28 x 5/8	32.80
CC-100-075		1	3/4	2	3	1/4-28 x 5/8	31.40
CC-100-100		1	1	2	3	1/4-28 x 5/8	29.00
CC-112-100		1 1/8	1	2 1/8	3 1/4	1/4-28 x 3/4	35.90
CC-112-112		1 1/8	1 1/8	2 1/8	3 1/4	1/4-28 x 3/4	34.70
CC-125-100		1 1/4	1	2 1/4	3 3/8	1/4-28 x 3/4	41.80
CC-125-125		1 1/4	1 1/4	2 1/4	3 3/8	1/4-28 x 3/4	38.40
CC-137-100		1 3/8	1	2 3/8	3 5/8	1/4-28 x 3/4	50.00
CC-137-137		1 3/8	1 3/8	2 3/8	3 5/8	1/4-28 x 3/4	44.70
CC-143-143		1 7/16	1 7/16	2 3/8	3 5/8	1/4-28 x 3/4	49.50
CC-150-100		1 1/2	1	2 1/2	3 3/4	1/4-28 x 3/4	57.40
CC-150-150		1 1/2	1 1/2	2 1/2	3 3/4	1/4-28 x 3/4	49.50
CC-175-175		1 3/4	1 3/4	3	4 1/2	5/16-24 x 1	90.00
CC-193-193		1 15/16	1 15/16	3 1/4	4 7/8	5/16-24 x 1	105.00
CC-200-200		2	2	3 1/4	4 7/8	5/16-24 x 1	107.00
CC-225-225		2 1/4	2 1/4	3 1/2	5	5/16-24 x 1	130.00

ONE-PIECE CLAMPING COUPLINGS RECESSED SCREW WITH KEYWAY **CC-SERIES**



- Recessed screw head provides an outside surface free of major projections
- High axial load and torque capacity
- Design fully engages the shaft without marring
- Greater axial holding power than set screw couplings
- Effective on both hard and soft shafts



For 3D Models & 2D Sales Drawings

DIMENSION
BORE, INCH

TOLERANCE
+0.003 / -0.000

PART NUMBER	PRODUCT SPECIFICATIONS								
	BLACK OXIDE STEEL	BORE	2ND BORE	OD	LENGTH	SCREW SIZE	KEYWAY SIZE	2ND KEYWAY SIZE	APPROX WEIGHT (OZ)
CC-037-037-KW		3/8	3/8	1 1/16	1 5/8	6-32 x 3/8	3/32	3/32	4.96
CC-050-050-KW		1/2	1/2	1 1/4	1 7/8	8-32 x 1/2	1/8	1/8	7.70
CC-062-062-KW		5/8	5/8	1 1/2	2 1/4	10-32 x 1/2	3/16	3/16	22.40
CC-075-075-KW		3/4	3/4	1 3/4	2 5/8	1/4-28 x 5/8	3/16	3/16	20.90
CC-087-087-KW		7/8	7/8	1 7/8	2 7/8	1/4-28 x 5/8	3/16	3/16	25.40
CC-100-100-KW		1	1	2	3	1/4-28 x 5/8	1/4	1/4	29.00
CC-112-112-KW		1 1/8	1 1/8	2 1/8	3 1/4	1/4-28 x 3/4	1/4	1/4	34.70
CC-125-125-KW		1 1/4	1 1/4	2 1/4	3 3/8	1/4-28 x 3/4	1/4	1/4	38.40
CC-137-137-KW		1 3/8	1 3/8	2 3/8	3 5/8	1/4-28 x 3/4	5/16	5/16	44.70
CC-143-143-KW		1 7/16	1 7/16	2 3/8	3 5/8	1/4-28 x 3/4	3/8	3/8	49.50
CC-150-150-KW		1 1/2	1 1/2	2 1/2	3 3/4	1/4-28 x 3/4	3/8	3/8	49.50
CC-175-175-KW		1 3/4	1 3/4	3	4 1/2	5/16-24 x 1	3/8	3/8	90.00
CC-193-193-KW		1 15/16	1 15/16	3 1/4	4 7/8	5/16-24 x 1	1/2	1/2	105.00
CC-200-200-KW		2	2	3 1/4	4 7/8	5/16-24 x 1	1/2	1/2	107.00
CC-225-225-KW		2 1/4	2 1/4	3 1/2	5	5/16-24 x 1	1/2	1/2	130.00