

TWO-PIECE CLAMPING COUPLINGS RECESSED SCREW WITH KEYWAY **2CC-SERIES**



- For use on keyed shafts
- Recessed screw head provides an outside surface free of major projections
- Easily installed where major disassembly would otherwise be required
- High axial load and torque capacity
- Design fully engages the shaft without marring
- Greater axial holding power than set screw and one-piece couplings
- Effective on both hard and soft shafts

PART NUMBER	PRODUCT SPECIFICATIONS								
	BLACK OXIDE STEEL	BORE	2ND BORE	OD	LENGTH	SCREW SIZE	KEYWAY SIZE	2ND KEYWAY SIZE	APPROX WEIGHT (OZ)
2CC-037-037-KW	3/8	3/8	1 1/16	1 5/8	6-32 x 3/8	3/32	3/32	4.96	
2CC-050-037-KW	1/2	3/8	1 1/4	1 7/8	8-32 x 1/2	1/8	3/32	8.11	
2CC-050-050-KW	1/2	1/2	1 1/4	1 7/8	8-32 x 1/2	1/8	1/8	7.90	
2CC-062-050-KW	5/8	1/2	1 1/2	2 1/4	10-32 x 1/2	3/16	1/8	13.60	
2CC-062-062-KW	5/8	5/8	1 1/2	2 1/4	10-32 x 1/2	3/16	3/16	22.50	
2CC-075-050-KW	3/4	1/2	1 3/4	2 5/8	1/4-28 x 5/8	3/16	1/8	22.00	
2CC-075-062-KW	3/4	5/8	1 3/4	2 5/8	1/4-28 x 5/8	3/16	3/16	22.00	
2CC-075-075-KW	3/4	3/4	1 3/4	2 5/8	1/4-28 x 5/8	3/16	3/16	22.00	
2CC-087-062-KW	7/8	5/8	1 7/8	2 7/8	1/4-28 x 5/8	3/16	3/16	27.40	
2CC-087-087-KW	7/8	7/8	1 7/8	2 7/8	1/4-28 x 5/8	3/16	3/16	26.00	
2CC-100-050-KW	1	1/2	2	3	1/4-28 x 5/8	1/4	1/8	27.40	
2CC-100-075-KW	1	3/4	2	3	1/4-28 x 5/8	1/4	3/16	29.10	
2CC-100-100-KW	1	1	2	3	1/4-28 x 5/8	1/4	1/4	29.10	
2CC-112-100-KW	1 1/8	1	2 1/8	3 1/4	1/4-28 x 3/4	1/4	1/4	35.90	
2CC-112-112-KW	1 1/8	1 1/8	2 1/8	3 1/4	1/4-28 x 3/4	1/4	1/4	34.20	
2CC-125-100-KW	1 1/4	1	2 1/4	3 3/8	1/4-28 x 3/4	1/4	1/4	42.40	
2CC-125-125-KW	1 1/4	1 1/4	2 1/4	3 3/8	1/4-28 x 3/4	1/4	1/4	42.40	
2CC-137-100-KW	1 3/8	1	2 3/8	3 5/8	1/4-28 x 3/4	5/16	1/4	45.20	
2CC-137-137-KW	1 3/8	1 3/8	2 3/8	3 5/8	1/4-28 x 3/4	5/16	5/16	45.20	
2CC-143-143-KW	1 7/16	1 7/16	2 1/2	3 3/4	1/4-28 x 3/4	3/8	3/8	49.50	
2CC-150-100-KW	1 1/2	1	2 1/2	3 3/4	1/4-28 x 3/4	3/8	1/4	57.40	
2CC-150-150-KW	1 1/2	1 1/2	2 1/2	3 3/4	1/4-28 x 3/4	3/8	3/8	49.50	
2CC-175-175-KW	1 3/4	1 3/4	3	4 1/2	5/16-24 x 1	3/8	3/8	90.00	
2CC-193-193-KW	1 15/16	1 15/16	3 1/4	4 7/8	5/16-24 x 1	1/2	1/2	105.00	
2CC-200-200-KW	2	2	3 1/4	4 7/8	5/16-24 x 1	1/2	1/2	110.00	
2CC-225-225-KW	2 1/4	2 1/4	3 1/2	5	5/16-24 x 1	1/2	1/2	130.00	



For 3D Models & 2D Sales Drawings

DIMENSION
BORE, INCH

TOLERANCE
+0.003 / -0.000

LARGE BORE TWO-PIECE CLAMPING COUPLINGS **H2CC-SERIES** RECESSED SCREW WITH KEYWAY



- Provides a higher torque capacity over cast iron couplings
- Lighter weight than traditional cast iron couplings
- Smaller OD ideal for constrained spaces
- Easily installed where major disassembly would otherwise be required

PART NUMBER	PRODUCT SPECIFICATIONS								
	BLACK OXIDE STEEL	BORE	2ND BORE	OD	LENGTH	SCREW SIZE	SCREW QTY	KEYWAY SIZE	2ND KEYWAY SIZE
H2CC-193-193-KW	1 15/16	1 15/16	3 5/8	6	3/8-24 x 1-1/4	8	1/2	1/2	11.60
H2CC-243-243-KW	2 7/16	2 7/16	4 3/8	7 1/2	1/2-20 x 1-1/2	8	5/8	5/8	20.50
H2CC-293-293-KW	2 15/16	2 15/16	5 1/8	9	1/2-20 x 1-1/2	10	3/4	3/4	32.80
H2CC-343-343-KW	3 7/16	3 7/16	6 1/8	10 1/2	5/8-18 x 2	8	7/8	7/8	56.20
H2CC-393-393-KW	3 15/16	3 15/16	6 7/8	12	5/8-18 x 2	10	1	1	79.40
H2CC-443-443-KW	4 7/16	4 7/16	7 3/8	13 1/2	5/8-18 x 2	12	1	1	97.80



For 3D Models & 2D Sales Drawings

DIMENSION
BORE, INCH

TOLERANCE
+0.003 / -0.000